North America's Leader in Hazardous Material Information Management

1905 Aston Avenue, Carlsbad, CA 92008 Phone (800) 451-8346 Fax (760) 602-8888

# MSDS PRODUCT INFORMATION

Date: 10/07/2005

To: MSDS Requester

From: 3E Company

Subject: The MSDS you have requested

### [ ] MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communicatin Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

#### [X] MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

#### [ ] MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

#### [ ] MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: ITW TACC

Product Name: Acoustical Sound Sealant (DISCONTINUED)

MATERIAL SAFETY DATA SHEET Printed: 05/06/98 For Coatings, Resins and Related Materials Revised: 01/30/98 SECTION I - PRODUCT IDENTIFICATION Manufacturer: TACC INTERNATIONAL CORP Information Phone: 781-878-7015
Air Station Industrial Park Emergency Phone: 800 424 9300
CHEMTREC Phone: 800 424 9300 02370 Hazard Ratings: Health - 1
none -> extreme Fire - 0
0 ---> 4 Reactivity - 0 Product Class: Trade Name : ACOUSTICAL SOUND SEALANT
Product Code : MH13000 C.A.S. Number: MIXTURE ! Personal Protection - G D.O.T. Hazard Class: UN #: Proper Shipping Name: NON-REGULATED Technical Name: SECTION II - HAZARDOUS INGREDIENTS Weight --- Exposure Limits ---- VP Ingredients CAS # % ACGIH/TLV OSHA/PEL mm HG SILICA, OUARTZ 14808-60-7 < 1. .1 mg/M3 .1 mg/M3 0 SECTION III - PHYSICAL DATA Boiling Range: 212

Evap. Rate: Slower than n-Butyl Acetate
Volatiles vol % 19.7

Wgt% 12.0

Wgt per gallon: 13.42 Pounds.

Spec. Gravity: 1.61104 Appearance: WHITE PASTE, ACRYLIC ODOR SECTION IV - FIRE AND EXPLOSION HAZARD DANGER Flammability Class: IIIB Flash Point: NONE F PMCC LEL: N/A UEL: N/A -EXTINGUISHING MEDIA Foam, dry chemical, carbon dioxide, water spray or fog. -SPECIAL FIREFIGHTING PROCEDURES Non-flammable (aqueous emulsion). After water evaporates, remaining material will burn. Breathing apparatus when fighting fires in enclosed areas. -UNUSUAL FIRE & EXPLOSION HAZARDS None known. SECTION V - HEALTH HAZARD DATA -PERMISSIBLE EXPOSURE LEVEL:

Page: 1

See Section II.

TACC INTERNATIONAL CORP Page: Material Safety Data Sheet for: ACOUSTICAL SOUND SEALANT (MH13000) SECTION V - HEALTH HAZARD DATA (cont.) -EFFECTS OF OVEREXPOSURE INGESTION: Unknown. INHALATION: Inhalation of mists may cause mild respiratory irritation. EYES: Liquid splashed into the eye may cause transient eye irritation. SKIN: May cause transient skin irritation. -FIRST AID: INGESTION: Call Poison Center immediately. INHALATION: Remove to fresh air. EYES: Flush with large amounts of water lifting upper and lower lids. Continue for at least 15 minutes. Get medical attention. SKIN: Remove contaminated clothing. Wash affected area with soap and water. Obtain medical attention if irritation persists. NOTE TO PHYSICIAN: Any treatment that might be required for overexposure should be directed at the control of symptoms and clinical conditions. SECTION VI - REACTIVITY DATA STABLITY: [ ] Unstable [x] Stable
HAZARDOUS POLYMERIZATION: [ ] May occur [x] Will not occur -INCOMPATIBILITY None known. -CONDITIONS TO AVOID: None known. -HAZARDOUS DECOMPOSITION PRODUCTS Burning, including when heated by welding or cutting, will produce smoke, carbon monoxide and carbon dioxide. SECTION VII - SPILL OR LEAK PROCEDURES -STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Confine to small area. Use absorbent to clean up. Place in container for disposal. -WASTE DISPOSAL METHOD Dispose in accordance with federal, state and local regulations. SECTION VIII - SPECIAL PROTECTION INFORMATION:

## -RESPIRATORY PROTECTION

If applied by spraying, use an appropriate, properly fitted NIOSH/MSHA approved respirator to remove the spray mist. Refer to OSHA regulations on respiratory protection.

TACC INTERNATIONAL CORP Page: 3 Material Safety Data Sheet for: ACOUSTICAL SOUND SEALANT (MH13000) SECTION VIII - SPECIAL PROTECTION INFORMATION: (cont.) -VENTILATION Natural ventilation should be adequate under normal conditions. -PROTECTIVE GLOVES Not likely to be needed. -EYE PROTECTION Safety glasses. Face shield as necessary if spraying. -OTHER PROTECTIVE EQUIPMENT: Not likely to be needed. SECTION IX - SPECIAL PRECAUTIONS -PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep from freezing. -OTHER PRECAUTIONS: Do not take internally. Close container after each use. Keep away from children. SECTION X - ADDITIONAL REGULATORY INFORMATION -SARA TITLE III SECTION 313 This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right To Know Act of 1986 and of 40 CFR 372: Percent by CAS# Chemical Name Weight None -PROP 65 (CARCINOGEN) WARNING: This product contains a chemical known to the state of California to cause cancer. 75-07-0 ACETALDEHYDE FORMALDE Chemical Name 14808-60-7 SILICA, QUARTZ -PROP 65 (TERATOGEN) WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm. CAS# Chemical Name -----None

Page: 4 TACC INTERNATIONAL CORP
Material Safety Data Sheet for: ACOUSTICAL SOUND SEALANT(MH13000)

SECTION X - ADDITIONAL REGULATORY INFORMATION (cont.)

-PROP 65 (BOTH CARCINOGEN AND TERATOGEN)
WARNING: This product may contain a chemical known to the state of
California to cause cancer or birth defects or other reproductive harm

CAS# Chemical Name

None

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of TACC International. The data on this sheet relates only to the specific material designated herein. TACC International assumes no legal responsibility for use or reliance upon these data.